

Mechanically Controlled Chicken Holding Unit

Technical Data Sheet

Updated: 2026-10-13

Dry and wet heating options keep cooked chicken warm before service.



Mechanically Controlled Chicken Holding Unit

Electric

OT-MKCHD 80/2 -S

Energy	Electric
DIMENSIONS	800x650x500
PACKING VOLUME (m³)	0.26
POWER / ENERGY	1,5 Kw/ 220 V
CAPACITY	2-1/1 GN down

OT-MKCHD 115/3 -S

Energy	Electric
DIMENSIONS	1150x650x500
PACKING VOLUME (m³)	0.37
POWER / ENERGY	3,5 Kw/ 380 V
CAPACITY	3-1/1 GN down

OT-MKCHD 150/4 -S

Energy	Electric
DIMENSIONS	1450x650x500
PACKING VOLUME (m³)	0.49
POWER / ENERGY	4 ,5Kw/ 380 V
CAPACITY	4-1/1 GN down

OT-MKCHD 180/5 -S

Energy	Electric
DIMENSIONS	1800x650x500
PACKING VOLUME (m³)	0.59
POWER / ENERGY	5,5 Kw/ 380 V
CAPACITY	5-1/1 GN down

OTX-MKCHD 80/2 -D

Energy	Electric
DIMENSIONS	800x650x950
PACKING VOLUME (m³)	0.54
POWER / ENERGY	2,5 Kw/ 220 V
CAPACITY	2-1/1GNd/2-2/3Gup
GROSS WEIGHT (kg)	38

OTX-MKCHD 115/3 -D

Energy	Electric
DIMENSIONS	1150x650x950
PACKING VOLUME (m³)	0.54
POWER / ENERGY	3,5 Kw/ 380 V
CAPACITY	3-1/1GNd/3-2/3Gup
GROSS WEIGHT (kg)	54

OTX-MKCHD 145/4 -D

Energy	Electric
DIMENSIONS	1450x650x950
PACKING VOLUME (m³)	1.52
POWER / ENERGY	5 Kw/ 380 V
CAPACITY	4-1/1GNd/4-2/3Gup
GROSS WEIGHT (kg)	125

OTX-MKCHD 180/5 -D

Energy	Electric
DIMENSIONS	1800x650x950
PACKING VOLUME (m³)	1.65
POWER / ENERGY	6 Kw/ 380 V
CAPACITY	5-1/1GNd/5-2/3Gup
GROSS WEIGHT (kg)	145

OTX-MKCHD 215/6 -D

Energy	Electric
DIMENSIONS	2150x650x950
PACKING VOLUME (m³)	1.52
POWER / ENERGY	8 Kw/ 380 V
CAPACITY	6-1/1GNd/6-2/3Gup
GROSS WEIGHT (kg)	125