

Fully Automatic Two-Tier Chicken Holding Unit

Technical Data Sheet

Updated: 2026-10-13

Dry and humid holding sections keep cooked chicken warm and ready for service in a two-tier unit.



Fully Automatic Two-Tier Chicken Holding Unit

Electric

OTX-PPCHD 150/3 -D

Energy	Electric
DIMENSIONS	1530x750x850/1030
GROSS WEIGHT (kg)	54
PACKING VOLUME (m³)	0.99
POWER / ENERGY	5 Kw/ 380 V
CAPACITY	down part 3 qts 44x50x4cm up part 3 qts 44x50x2.5cm

OTX-PPCHD 180/4 -D

Energy	Electric
DIMENSIONS	1800x750x850/1030
GROSS WEIGHT (kg)	125
PACKING VOLUME (m³)	1.28
POWER / ENERGY	6 Kw/ 380 V
CAPACITY	down part 4 qts 44x50x4cm up part 4 qts 44x50x2.5cm

OTX-PPCHD 237/5 -D

Energy	Electric
DIMENSIONS	2370x850x850/1030
GROSS WEIGHT (kg)	145
PACKING VOLUME (m³)	1.65
POWER / ENERGY	8 Kw/ 380 V
CAPACITY	down part 5 qts 44x50x4cm up part 5 qts 44x50x2.5cm